

STÜWA Kiesbelag-Filter

Technische Information

| DN | Zoll | Innen ∅ | Außen - ∅ | Wandstärke des PVC-Rohres | Außen - ∅ über Kiesbelag ca. mm | Kiesbelag- stärke mm | Gewicht ca. kg/ m |
|-----|------|------------|-----------|---------------------------------|--|----------------------------|----------------------|
| 35 | 1¼" | 34,5 | 41,5 | 3,5 | 63 | 10,5 | 3,1 |
| 40 | 1½" | 41 | 48 | 3,5 | 75 | 13,5 | 4,8 |
| 50 | 2" | 52 | 60 | 4,0 | 92 | 16,0 | 6,1 |
| 80 | 3" | 80 | 88 | 4,0 | 121 | 16,5 | 10,0 |
| 100 | 4" | 103 | 113 | 5,0 | 143 | 15,0 | 11,5 |
| 115 | 4½" | 115 | 125 | 5,0 | 157 | 16,0 | 13,5 |
| 125 | 5" | 127 | 140 | 6,5 | 172 | 16,0 | 15,14 |
| 150 | 6" | 150 | 165 | 7,5 | 196 | 15,5 | 16,5 |
| 175 | 7" | 178 | 195 | 8,5 | 226 | 15,5 | 23,0 |
| 200 | 8" | 205 | 225 | 10,0 | 261 | 18,0 | 30,0 |
| 250 | 10" | 255 | 280 | 12,5 | 316 | 18,0 | 41,0 |
| 300 | 12" | 301 | 330 | 14,5 | 366 | 16,0 | 48,5 |
| 350 | 14" | 365 | 400 | 17,5 | 436 | 18,0 | 65,0 |
| 400 | 16" | 411 | 450 | 19,5 | 482 | 16,0 | 74,0 |

Werkstoff : PVC-hart nach DIN 4925

| | | | |
|------------------------|---------|------------------|-------------------|
| Schlitzweiten : | Körnung | 0,7 - 1,2 | Sw 0,75 mm |
| | Körnung | 1 - 2 | Sw 1,0 mm |
| | Körnung | 2 - 3 | Sw 1,5 mm |
| | Körnung | 3 - 5 | Sw 2,0 mm |

Verbindung : nach DIN 4925

| | | |
|--------------------|--|-------------|
| Baulängen : | DN 35, 40, 50 | 1,0m |
| | DN 80 - DN 400 (1m-Baulängen möglich) | 2,0m |